

Binary transition metal oxide complexes (BTMOCs) in three-dimensional (3D) layered structures show great promise as electrodes for supercapacitors (SCs) due to their diverse oxidation states, which contribute to high specific capacitance. However, the synthesis of BTMOCs with 3D structures remains challenging yet crucial for their application. In this study, ...

Recently, Favalli et al. have demonstrated that scintillating particle composite detectors can provide robust performance in high neutron flux environments and outlined the value of heterogeneous composite detectors. 1 For practical applications in nuclear security and safeguards, however, it is highly advantageous for the heterogeneous composite to be all-solid ...

Current energy storage devices are delicate, hold limited capacity, and struggle to achieve maximum energy conversion efficiency. While breakthroughs are unlikely in the near future, advancements can come from either exploring new materials or integrating with existing systems. We propose a novel approach: a hybrid material development for a hybrid mode of ...

Single-crystalline films (SCFs) of the LuAG: Ce garnet grown using the liquid-phase epitaxy method onto YAG single-crystal (SC) substrates were investigated for possible applications as composite thermoluminescent (TL) detectors. Such detectors may help to register the different components of ionizing radiation fields with various penetration depths, e.g., heavy ...

Furthermore, another important parameter to be studied in the novel flexible and foldable composite detector is the Gamma Rejection Ratio (GRR), which is the intrinsic response of the neutron ...

Aiming at the problem that traditional fire detectors can only detect single hazard feature, a domestic smoke-temperature composite detector based on HWD32 is designed. The functional requirements of the detector are proposed, the hardware circuit and software algorithm of the detector are designed, and the functional performance tests of smoke and temperature sensing ...

The comprehensive performance of ferroelectric ceramic materials is a significant factor limiting the practical application. In this work, a novel strategy of constructing diphasic compounds is proposed to significantly enhance the energy storage properties of $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based ceramics. A composite ceramic of pyrochlore phase $\text{Sm}_{2}\text{Ti}_{2}\text{O}_7$ modified ...

Different scintillation decay constants are used to identify energy depositions in two materials constituting the composite scintillator. Geant4 simulations of the neutron thermalization and capture process were conducted, finding a mean capture time of approximately 2.6 ms for both DD and DT neutrons.

Li et al. [5] prepared a composite material for thermal energy storage with polyethylene glycol and ZSM-5. The mesoporous ZSM-5 was taken as a supporting material and vacuum impregnation method was employed.

... with a unique fingerprint of the absorbed radiation of the sample molecules in the range of 4000-400 cm^{-1} at the detector. 2.3.5 ...

Carbon ion radiotherapy (C-ion RT) has the advantages of a depth-to-dose curve with a pronounced dose maximum, the so-called Bragg peak, and the high biological properties compared to conventional X-ray radiotherapy. This allows the dose distribution to be highly conformal to the tumor region while sparing healthy surrounding tissue (Ohno, 2013). ...

Abstract Devices that harvest energy are crucial for reducing reliance on energy transmission and distribution systems. This helps minimize energy loss and mitigate environmental impacts. In this study, we focused on manufacturing nanocomposites using various ratios of polyvinylidene fluoride (PVDF) and thermoplastic polyurethane (TPU). PVDF, a ...

In the field of energy storage, ... This carbon fiber/resin composite has been employed as an energy efficient heating element ... Raman spectroscopy was carried out using a Renishaw InVia Reflex Micro Raman Spectrometer equipped with the CCD detector at room temperature and in air. Green laser (excitation line 514 nm) was used to excite the ...

With the sharp increase in modern energy consumption, phase change composites with the characteristics of rapid preparation are employed for thermal energy storage to meet the challenge of energy crisis. In this study, a NaCl-assisted carbonization process was used to construct porous *Pleurotus eryngii* carbon with ultra-low volume shrinkage rate of 2%, ...

This manuscript summarizes recent results on the development of composite luminescent materials based on the single-crystalline films and single crystals of simple and mixed garnet compounds obtained by the liquid-phase epitaxy growth method. Such composite materials can be applied as scintillating and thermoluminescent (TL) detectors for radiation monitoring of ...

The energy storage system plays an increasingly important role in solving new energy consumption, enhancing the stability of the power grid, and improving the utilization efficiency of the power distribution system. arouse people's general attention s application scale is growing rapidly, and the safety of energy storage power stations has also attracted ...

Thermal energy storage technology, ... (XRD) experiments were performed on a Rigaku D/max-gb X-ray diffractometer with a monochromatic detector. ... Q2000) was used to investigate the thermal energy storage properties of the prepared composite form-stable PCMs over the temperature of 10-80 ...

1. Introduction. Phase change material (PCM) is a kind of material which absorbs and releases latent heat through reversible phase transition in a limited temperature range [1] terms of building energy, the latent heat storage characteristics of PCMs can be applied to passive building heat storage, so as to adjust the indoor temperature to achieve the ...

The 0.25 vol% ITIC-polyimide/polyetherimide composite exhibits high-energy density and high discharge efficiency at 150 °C (2.9 J cm⁻³, 90%) and 180 °C (2.16 J cm⁻³, 90%). This work provides a scalable design idea for high ...

This work concerns with thermal energy storage (TES), more specifically, latent heat based thermal energy storage (LHTES). LHTES typically uses liquid-solid phase transition of a material, the so-called phase change material (PCM), and the advantages of PCM based TES lie in its high energy density and isothermal charging/discharging processes [6].

Solid-liquid phase-change materials (PCMs) are a type of latent heat-storage material. They can absorb and store a large quantity of thermal energy from different heat sources, such as solar and waste heat, and release it in a small range of temperature fluctuation through reversible solid-liquid phase transitions [1, 2] ch a distinguished feature enables ...

Zwinsoft ZWIN-ESG1006 three-in-one composite gas detector is an early fire warning ? product mainly used in electrochemical energy storage battery PACK. This product is usually installed on the outside or inside of the battery PACK box, or on the high wall or ceiling of a small energy storage battery cabinet. This product has RS485

The majority (73 %) of the UK's industrial energy demand is for heating, with 35 % for steam generation alone [1] sides the associated emissions of greenhouse gases, industrial heating processes give rise to a significant amount of waste heat, as high as 50 % + in sectors like steel and glass [2].Thus, there is a significant potential for the emission reduction through waste ...

Dielectric capacitors have garnered significant attention in recent decades for their wide range of uses in contemporary electronic and electrical power systems. The integration of a high breakdown field polymer matrix with various types of fillers in dielectric polymer nanocomposites has attracted significant attention from both academic and commercial ...

This paper presents a novel shape-stable phase change material (PCM) composite for thermal energy storage applications. The formulation of the material consists of the components: eutectic nitrate (NaNO₃-KNO₃) as thermal storage material, ... (SE) detector and high vacuum (HV), at an acceleration voltage of 10 kV, with a spot size of 3.0 nm.

In this review, we discuss the recent advances in the synthesis and application of CPs and graphene-based composites in electrochemical energy storage devices (supercapacitors) and electrochemical sensors. In the ...

The above studies found that the PANI/MnO₂ composite film has greatly improved energy storage performance and electrochemical cycle stability compared with PANI film, which supply a possibility to achieve high capacitance and long-lived cycling stability for electrochromic energy storage devices (EESD)

with PANI/MnO₂ ...

Thus, a great deal of attention has been devoted in recent years, in addressing the energy challenges in buildings through the integration of thermal energy storage (TES) systems using phase change materials (PCMs) [5, 13, 14] short, the PCM is a type of material which can store and release the thermal energy through a phase transition process at near ...

Mid-infrared (MIR, 2.5-25 μm) detectors that can convert MIR radiation into electrical signals have been employed in many fields 1, such as in digital imaging 2, wearable devices 3, and energy ...

Read the latest articles of Journal of Energy Storage at ScienceDirect , Elsevier's leading platform of peer-reviewed scholarly literature ... select article Hydrogen gas diffusion behavior and detector installation optimization of lithium ion battery energy-storage cabin ... Finned coil-type energy storage unit using composite inorganic ...

Web: <https://www.eriabv.nl>

Chat online: <https://tawk.to/chat/667676879d7f358570d23f9d/1i0vbu11i?web=https://www.eriabv.nl>